



The laser-based snow depth sensor Lufft SHM31 stands for millimeter-accurate snow level detection over long distances in all weather conditions without any maintenance, due to opto-electronic/laser based rangefinder technology.

- **Parameters measured**
Snow depth
- **Measurement technology**
opto-electronic measuring technique (rangefinder; laser distance sensor) with eye-safe laser
- **Product highlights**
Determination of snow depth over long distances, heating options allow high quality measurements in all weather conditions, simplified installation due to automatic inclination angle compensation
- **Interfaces**
RS485 & RS232 with UMB, UMB-ASCII 2.0 & SDI12 protocol
- **Article number**
8365.30

Millimeter-accurate snow levels in all weather conditions: The SHM 31 operates with a visible, easy-to-measure measuring beam. The snow depth is given up to 15 meters within seconds, millimeter-accurate and reliable. Various heating functions significantly extend the lifetime of the laser diode and allow high-quality measurement data in all weather conditions. Regular maintenance becomes redundant with the SHM 31. A very robust

Technical Data

Snow Depth Sensor SHM31



housing and an elaborate operation principle allows almost no maintenance work throughout the lifetime of the sensor.

General	
Dimensions (LxWxH)	302mm × 130mm × 234mm
Weight	2,35 kg
Operating parameters	
Temperature range	-40°C...+50 °C
Relative humidity	0%...100%

Measuring parameters	
Snow Depth	0 ... 15 m
Mounting distance to surface	0,1 ... 16 m
Accuracy (snow depth) ²	± (5 mm + 0.06 %)
Repeatability	0.6 mm
Intermediate precision/ reproducibility	5 mm

Data-interfaces	
RS485	ASCII, UMB protocol
RS232	ASCII protocol
SDI-12	SDI-12 protocol
Data transfer mode	Polling (UMB, ASCII, SDI-12); Auto telegram output (ASCII)

Electrical parameters	
typ. power consumption at 24 Vdc and 10 s laser measurement interval	without heater: approx. 0.7 W; with window heating: approx. 3.4 W
Power supply	12, 24 VDC
Maximum power consumption(connecting power with heater on)	18 W

Safety	
Laser classification	Laser class 2 (IEC 60825-1:2014)
Protection class	IP68
EMC	EN 61326-1:2012 (industrial standard)
EC	2014/30/EU & RoHS 2011/65/EU