



High-precision reference measurement standard for industrial temperature calibrations

- **Parameters measured**
Relative humidity, Temperature
- **Measurement technology**
Temperature / NTC (Negative Temperature Coefficient); Rel. humidity / Capacitive
- **Product highlights**
Excellent accuracy of temperature and relative humidity. Display of calculations and statistical functions.
- **Interfaces**
USB (Cable and SmartGraph3 software included)
- **Article number**
5700.00

The powerful and compact handheld device with state-of-the-art and robust design. Excellent accuracy. The high-resolution color screen displays rel. humidity, temperature and dew point. Excellent readability. The calibration function (offset correction) guarantees the long-term use without compromising the accuracy.

IMPORTANT: XC200 Handheld Device is discontinued

General

Dimensions	170 x 60 x 35 mm
Weight	Approx. 250 g

Storage conditions

Permissible ambient temperature	-20...60 °C
Operating rel. humidity	<95 % relative humidity non - condensing

Operating conditions

Operating temperature	-20...50 °C
Operating rel. humidity	<90 % RH
Admissible height above absolute altitude	3000 m

Power supply

Power supply	5.5 V ± 10 % DC, max. 200 mA
Power consumption active	Approx. 70 mA
Passive power consumption	Approx. 40 µA
Battery life	Approx. 24 h (2.6 Ah battery capacity)
Calculations	Dew point temperature °C or °F Absolute humidity g/m ³ Mixed ratio g/kg or gr/lb
Functions	Statistical calculations MAX, MIN, HOLD, AVG, ACT Temperature correction and humidity correction factors (offset) Power saving functions

Relative humidity

Principle	Capacitive
Measuring range	0 ... 100 % RH
Unit	% RH
Accuracy	±2% RH
Resolution	0.1

Temperature

Principle	NTC
Measuring range	-20 ... 50 °C
Unit	°C
Accuracy	± 0.2°C (0...40°C) otherwise ± 0.4°C
Resolution	0.1