



### Compact universal weighing precipitation gauge

- **Parameters measured**  
Cumulative precipitation, precipitation intensity, bucket content in real time and non real time
- **Measurement range**  
Weighing principle
- **Product Highlights**  
Compact all-weather precipitation gauge for 2-inch pedestals, highly accurate, meets WMO requirements (Guidelines No. 8), nearly maintenance-free, lifetime calibrated
- **Interface**  
SDI-12, RS-485, impulse, status
- **Article number**  
70.030.001.9.0.EN

The OTT Pluvio<sup>2</sup> S weighing precipitation gauge measures the intensity and cumulative precipitation in a broad measuring range from 0 to 3,000 mm/h.

The professional rain gauge is a further development of the tried-and-tested OTT Pluvio<sup>2</sup>, with state-of-the-art technology in a compact design that captures up to 400 mm of precipitation on a collecting area of 200 cm<sup>2</sup>. It is virtually maintenance-free, fits onto 2-inch pedestals, needs little space and can replace conventional rain gauges or tipping buckets without any structural work.

Recordable precipitation	Liquid, solid, and mixed
Recordable precipitation amount	400 mm (approx. 8 l)
Collecting area	200 cm <sup>2</sup>
Measurement method	Weighing measurement method
Sensor element	Hermetically sealed load cell

### Measuring ranges

Precipitation	0 ... 50 mm/min or 0 ... 3000 mm/h
Cumulative precipitation threshold at 60 min. collection	0.03 mm
Precipitation intensity threshold	0.1 mm/h or 6 mm/h

### Accuracy (at -25°C ... +45°C)

Amount	± 0.1 mm or ±1% of measured value
Intensity	± 0.1 mm/min or ± 6 mm/h or ±1% of measured value

### Resolution

SDI-12 and RS-485	Amount: 0.001 mm Intensity: 0.001 mm/min or 0.01 mm/h
Impulse output	0.05/0.1/0.2 mm, adjustable

### Query interval

Amount	6 sec ... 60 min
Intensity	1 min

### Output delay

Real-time	< 1 min
Non-real-time (filtered values)	5 min

### Measurement output

Measured data	Intensity RT, amount RT/NRT, amount NRT, amount total NRT, bucket content RT and NRT, temperature of load cell
Status output	Pluvio <sup>2</sup> S status, heating status (if present)

### Electrical data

Serial interfaces	SDI-12 V1.3, RS-485 (2- or 4-wire), SDI-12 protocol and command line mode (ASCII)
Digital outputs (2/5 Hz)	Impulse 0.05/0.1/0.2 mm (adjustable); status 0 ... 120
USB (2.0)	Impulse mode
Power supply	5.5 ... 28 V DC, secured against reverse polarity
Current consumption (without heating)	Typically 9.2 mA at 12 VDC
Power consumption (without heating)	< 110 mW

### Ring heating, optional

Power supply	12 ... 28 VDC, typ. 12/24 VDC, secured against reverse polarity
Heating capacity	24 VDC / max. 50 W, temperature control range 45 K (wind speed 0 m/s); 12 VDC / max. 12.5 W, temperature control range 12 K (wind speed 0 m/s)
Modes of operation of heater control system	Disabled, continuously enabled, continuously enabled within a specified temperature range, US NWS standard (time-controlled), enabled in case of precipitation (adjustable after-run time)
Operating range of orifice rim heater	-40 °C ... + 60 °C (ambient temperature)

### Mechanical data

#### Dimensions and weight

Pluvio <sup>2</sup> S	288 mm x 651 mm (Ø x h)
Pedestal	Ø 2" / 50 ... 60 mm
Weight	Approx. 7.8 kg (empty bucket)

#### Material

Base plate	Stainless steel/aluminium
Collecting bucket/bucket support/pipe housing	ASA, UV resistant

#### Environmental conditions

Temperature, in operation	-40 ... +60 °C
Temperature, storage	-40 ... +70 °C
Relative humidity	0 ... 100 % rF (non-condensing)

#### Protection and Standards

Pipe housing closed	IP65
Pipe housing open	IP63
Load cell	IP67
EMC	2004/108/EG; EN 61326-1:2013
Salt resistance	EN 60068-2-11